

660

Barrier Direct To Metal

High productivity solution for bare metal surfaces

When speed is of the essence, **660 Barrier Direct To Metal** is the fast and efficient way to protect bare metal surfaces. This unique two-pack polyurethane technology allows you to eliminate the time-consuming traditional process of applying layers of primer and waiting for it to cure.

660 Barrier Direct To Metal, from PPG Light Industrial Coatings, has been specially formulated for application directly onto suitably prepared substrates.

In situations where long term durability and weathering resistance are non-critical, this high productivity application direct to metal process is perfect for getting the job done quickly and efficiently.

- High productivity one layer system eliminates the need for primer
- Provides good adhesion to a variety of substrates, including bare steel, aluminium, galvanised steel and fibre-reinforced plastic
- Good gloss level – approximately 80 to 85% at 60° gloss.
- Good chemical and abrasion resistance
- High film-build – up to 160 micron wet-film
- Special formulation features anti-corrosive pigmentation
- Excellent opacity
- Easy application via conventional or airless spray equipment
- All AS2700 and RAL Classic colours available



PPG know-how and support

Nothing beats the ability to get expert assistance when you need it. The Light Industrial Coatings Technical Support Team is just a phone call away and they will be happy to help you choose the correct products for your application and provide technical advice.

Locally made for local conditions

Made in Australia under strict quality control with high quality ingredients, **660 Barrier Direct To Metal** provides superior performance under local conditions.



PPG Industries Australia Pty Ltd,
Locked Bag 888, Clayton South, Victoria 3169.
McNaughton Road, Clayton, Victoria 3168, Australia.
Tel: 1800 076 466 Fax: 1800 800 819



PPG Industries
Light Industrial Coatings